

9/16" Ionoplast

Laminated Glass

Each FHC Door Rail

is Factory Designed

to Allow for Vertical

Adjustment of Plus

1/8" or Minus 1/16"

Rail Setting Blocks.

Solid One Piece Rail Housing

3-1/8" Overall Deduction

(Includes 1/4" Standard Clearance)

Optional

Weatherstripping

Item No. RWS36

Seal Sold Separately

PAS Pivot Alignment

System With Hardware

Mounting Block Allows 3/8" Adjustments

With Our Included Door

FHC-ADVANCE SERIES FRAMELESS GLASS ENTRANCE SYSTEM

CSI DIVISION 08 SECTION 08 4210

Advance HERC DOOR Rail

4" Tapered Door Rail 1/2" or 9/16" Tempered Glass

- · Patent Pending UNITIZING GASKET / Dual-Inclined Control Surfaces
- · Easiest and Fastest Rail to Install in the Industry
- New Modern Crisp Corner Design
- For 1/2" Monolithic Tempered and 9/16" Laminated Tempered Glass
- · Class 1 Anodizing UV Stable Finishes That Will Not Fade
- New Improved Pivot Alignment System "PAS" Included With Each Rail
- · Increased Glass Bite Improves Holding Strength and Aesthetics
- · Solid One Piece Aluminum Housing
- State of the Art Solid Forged Brass Plated End Caps With Premium Finishes

60 Degree

A.D.A Compliant

Tapered Top Edge

New Innovative Built-In

R4T12DUL

Anti-Clamshell Pad

- · New Innovative Anti-Clamshell Pad End Cap
- · Available With or Without Lock
- · Available In a Wide Range of Architectural Finishes

Patent Pending **Dual-Inclined Bearing** Surface Controls Angularity and Self Centering of the Rail

Patent Pending Unitizing Clamping Gasket

Cladding Included on Stainless Steel and Brass Finishes


R4T12DU

Innovative Concealed Actuation Hardware Allows for Uninterrupted Hardware Mounting

2-7/8" Glass Deduction

1/4" Clearance Standard





PRODUCT INFO/SPECIFICATIONS:

- CSI Format Specifications are Available for Download
- End Caps are Included with Every Door Rail
- Door Rails With Locks are Supplied Prepped and Installed, Keyed Cylinders, and Thumbturns are Sold Separately

Door Rail Top View

1/16" Setting Blocks

(Installed at edge of door rail at FHC Factory)

- FHC Follows GANA Guidelines for Maximum Door Height and Widths. Reference the FHC Herc-Door Sizing Guidelines.

CUSTOM LENGTH 4" TAPERED DOOR RAILS - SPECIFICATION AS SUPPLIED BY CUSTOMER

WITHOUT LOCK ITEM NO.	WITH LOCK ITEM NO.	DESCRIPTION
R4T12PSC	R4T12PSLC	Custom Tapered Door Rail Length Polished Stainless Steel
R4T12BSC	R4T12BSLC	Custom Tapered Door Rail Length Brushed Stainless Steel
R4T12SAC	R4T21SALC	Custom Tapered Door Rail Length Satin Anodized
R4T12MBC	R4T12MBLC	Custom Tapered Door Rail Length Matte Black (Powder Coat)
R4T12DUC	R4T12DULC	Custom Tapered Door Rail Length Dark Bronze Anodized
R4T12PTC	R4T12PTLC	Custom Tapered Door Rail Length Custom Paint Color

CARE & CLEANING

Brushed Stainless Steel, Polished Stainless Steel or Class 1 Anodized Finishes should be cleaned with a foam spray cleaner, such as: FHC GW19 Ammonia Free Cleaner. GW19 cleaner will assist with removing fingerprints, grease and water splatter. GW19 cleaner will also preserve the durable factory finish and can be wiped with a clean, dry cloth. FHC Lint Free Shop Wipes FHC3255 are recommended. These high performance wipes maintain their strength wet or dry and will not scratch the surface.



Tapered Door Rail 35-3/4" Long Dark Bronze Anodized



Toll Free: (888) 295-4531 | Fax: 323 336-8307 | Web: fhc-usa.com P.O. Box 1906, South Gate, CA 90280